



# SAFETY DATA SHEET

## 1. Product and Company Identification

<b>Product identifier</b>	<b>Cutek Extreme</b>
<b>Other means of identification</b>	Not available
<b>Recommended use</b>	Decorative Wood Coating for Exterior Use
<b>Recommended restrictions</b>	None known.
<b>Manufacturer information</b>	Deck Source Inc. 647 Welham Road, Unit 11 Barrie, ON L4N 0B7 CA Phone: 1-844-442-8835 Emergency Phone: 613-996-6666 (CANUTEC)
<b>Supplier</b>	See above.

## 2. Hazards Identification

<b>Physical hazards</b>	Flammable liquids	Category 4
<b>Health hazards</b>	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2
	Sensitization, skin	Category 1
	Reproductive toxicity	Category 2
	Aspiration hazard	Category 1
<b>Environmental hazards</b>	Not classified.	
<b>WHMIS 2015 defined hazards</b>	Not classified	
<b>Label elements</b>		



**Signal word** Danger

**Hazard statement** Combustible liquid. May be fatal if swallowed and enters airways. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Suspected of damaging fertility or the unborn child.

**Precautionary statement**

**Prevention** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Wear protective gloves, protective clothing, eye protection and face protection. Wash thoroughly after handling. Avoid breathing mist or vapor. Contaminated work clothing should not be allowed out of the workplace.

**Response** In case of fire: Use appropriate media to extinguish.  
IF SWALLOWED: Immediately call a POISON CENTER or doctor. Do NOT induce vomiting.  
IF ON SKIN: Wash with plenty of water. Specific treatment (see information on this label). If skin irritation or rash occurs: Get medical attention. Take off contaminated clothing and wash it before reuse.  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.  
IF exposed or concerned: Get medical attention.

**Storage** Store in a well-ventilated place. Store locked up.

**Disposal** Dispose of container in accordance with local, regional, national and international regulations.

**WHMIS 2015: Health Hazard(s) not otherwise classified (HHNOC)** None known

**WHMIS 2015: Physical Hazard(s) not otherwise classified (PHNOC)** None known

**Hazard(s) not otherwise classified (HNOC)** None known.

**Supplemental information** None.

### 3. Composition/Information on Ingredients

#### Mixture

Chemical name	Common name and synonyms	CAS number	%
3(2H)-Isothiazolone, 4,5-dichloro-2-octyl-		64359-81-5	0.1-1*
Copper(II) 8-hydroxyquinolate		10380-28-6	0.1-1*
Distillates (petroleum), hydrotreated light paraffinic		64742-55-8	45-70*
Hexanoic acid, 2-ethyl-, zirconium salt		22464-99-9	0.1-1*
Naphtha (petroleum), hydrotreated heavy		64742-48-9	10-30*
Paraffin wax		8002-74-2	1-5*
Phosphoric acid, 2-ethylhexyl ester		12645-31-7	5-10*
Slack wax (petroleum)		64742-61-6	1-5*
Xylene		1330-20-7	0.1-1*

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

**Composition comments** US GHS: The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.  
\*CANADA GHS: The exact percentage (concentration) of composition has been withheld as a trade secret.

### 4. First Aid Measures

<b>Inhalation</b>	If symptoms develop move victim to fresh air. If symptoms persist, obtain medical attention.
<b>Skin contact</b>	IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical attention. Specific treatment (see information on this label). Take off contaminated clothing and wash it before reuse.
<b>Eye contact</b>	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.
<b>Ingestion</b>	IF SWALLOWED: Immediately call a POISON CENTER or doctor. Do NOT induce vomiting.
<b>Most important symptoms/effects, acute and delayed</b>	Aspiration may cause pulmonary edema and pneumonitis. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.
<b>Indication of immediate medical attention and special treatment needed</b>	Provide general supportive measures and treat symptomatically. Symptoms may be delayed.
<b>General information</b>	IF exposed or concerned: Get medical advice. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse. Avoid contact with eyes and skin. Keep out of reach of children.

### 5. Fire Fighting Measures

<b>Suitable extinguishing media</b>	Dry chemical powder. Carbon dioxide. Foam.
<b>Unsuitable extinguishing media</b>	Do not use water jet as an extinguisher, as this will spread the fire.
<b>Specific hazards arising from the chemical</b>	The product is combustible, and heating may generate vapors which may form explosive vapor/air mixtures. During fire, gases hazardous to health may be formed.
<b>Special protective equipment and precautions for firefighters</b>	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
<b>Fire-fighting equipment/instructions</b>	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.
<b>Specific methods</b>	Use standard firefighting procedures and consider the hazards of other involved materials.
<b>General fire hazards</b>	Combustible liquid.
<b>Hazardous combustion products</b>	May include and are not limited to: Oxides of carbon.

---

## 6. Accidental Release Measures

---

### Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

### Methods and materials for containment and cleaning up

Use water spray to reduce vapors or divert vapor cloud drift. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. The product is immiscible with water and will spread on the water surface. Prevent entry into waterways, sewer, basements or confined areas.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

### Environmental precautions

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground. Do not discharge into lakes, streams, ponds or public waters.

---

## 7. Handling and Storage

---

### Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from open flames, hot surfaces and sources of ignition. When using do not smoke. Avoid breathing mist or vapor. Avoid contact with eyes, skin, and clothing. Pregnant or breastfeeding women must not handle this product. Provide adequate ventilation. Avoid prolonged exposure. Wear appropriate personal protective equipment. Wash thoroughly after handling. Use good industrial hygiene practices in handling this material. When using do not eat or drink.

### Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS). Keep out of reach of children.

---

## 8. Exposure Controls/Personal Protection

---

### Occupational exposure limits

#### Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)

Components	Type	Value	Form
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
Hexanoic acid, 2-ethyl-, zirconium salt (CAS 22464-99-9)	STEL	10 mg/m3	
	TWA	5 mg/m3	
Naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9)	TWA	1590 mg/m3	
		400 ppm	
Paraffin wax (CAS 8002-74-2)	TWA	2 mg/m3	Fume.
Xylene (CAS 1330-20-7)	STEL	651 mg/m3	
		150 ppm	
	TWA	434 mg/m3	
		100 ppm	

---

**Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)**

Components	Type	Value	Form
Hexanoic acid, 2-ethyl-, zirconium salt (CAS 22464-99-9)	STEL	10 mg/m3	
	TWA	5 mg/m3	
Paraffin wax (CAS 8002-74-2)	TWA	2 mg/m3	Fume.
Xylene (CAS 1330-20-7)	STEL	150 ppm	
	TWA	100 ppm	

**Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)**

Components	Type	Value	Form
Copper(II) 8-hydroxyquinolate (CAS 10380-28-6)	TWA	1 mg/m3	Dust and mist.
		0.2 mg/m3	Fume.
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	TWA	5 mg/m3	Inhalable fraction.
Hexanoic acid, 2-ethyl-, zirconium salt (CAS 22464-99-9)	STEL	10 mg/m3	
	TWA	5 mg/m3	
Paraffin wax (CAS 8002-74-2)	TWA	2 mg/m3	Fume.
Xylene (CAS 1330-20-7)	STEL	150 ppm	
	TWA	100 ppm	

**Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)**

Components	Type	Value	Form
Hexanoic acid, 2-ethyl-, zirconium salt (CAS 22464-99-9)	STEL	10 mg/m3	
	TWA	5 mg/m3	
Naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9)	TWA	525 mg/m3	
Paraffin wax (CAS 8002-74-2)	TWA	2 mg/m3	Fume.
Xylene (CAS 1330-20-7)	STEL	150 ppm	
	TWA	100 ppm	

**Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment)**

Components	Type	Value	Form
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
Hexanoic acid, 2-ethyl-, zirconium salt (CAS 22464-99-9)	STEL	10 mg/m3	
	TWA	5 mg/m3	
Naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9)	TWA	1590 mg/m3	
		400 ppm	
Paraffin wax (CAS 8002-74-2)	TWA	2 mg/m3	Fume.
Xylene (CAS 1330-20-7)	STEL	651 mg/m3	
		150 ppm	
	TWA	434 mg/m3	

**Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment)**

<b>Components</b>	<b>Type</b>	<b>Value</b>	<b>Form</b>
		100 ppm	
<b>US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)</b>			
<b>Components</b>	<b>Type</b>	<b>Value</b>	<b>Form</b>
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	PEL	5 mg/m3	Mist.
Hexanoic acid, 2-ethyl-, zirconium salt (CAS 22464-99-9)	PEL	5 mg/m3	
Naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9)	PEL	400 mg/m3	
		100 ppm	
Xylene (CAS 1330-20-7)	PEL	435 mg/m3	
		100 ppm	
<b>US. ACGIH Threshold Limit Values</b>			
<b>Components</b>	<b>Type</b>	<b>Value</b>	<b>Form</b>
Copper(II) 8-hydroxyquinolate (CAS 10380-28-6)	TWA	1 mg/m3	Dust and mist.
		0.2 mg/m3	Fume.
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	TWA	5 mg/m3	Inhalable fraction.
Hexanoic acid, 2-ethyl-, zirconium salt (CAS 22464-99-9)	STEL	10 mg/m3	
	TWA	5 mg/m3	
Paraffin wax (CAS 8002-74-2)	TWA	2 mg/m3	Fume.
Xylene (CAS 1330-20-7)	STEL	150 ppm	
	TWA	100 ppm	
<b>US. NIOSH: Pocket Guide to Chemical Hazards</b>			
<b>Components</b>	<b>Type</b>	<b>Value</b>	<b>Form</b>
Copper(II) 8-hydroxyquinolate (CAS 10380-28-6)	TWA	1 mg/m3	Dust and mist.
		0.1 mg/m3	Fume.
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
Hexanoic acid, 2-ethyl-, zirconium salt (CAS 22464-99-9)	STEL	10 mg/m3	
	TWA	5 mg/m3	
Naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9)	TWA	400 mg/m3	
		100 ppm	
Paraffin wax (CAS 8002-74-2)	TWA	2 mg/m3	Fume.
Xylene (CAS 1330-20-7)	STEL	655 mg/m3	
		150 ppm	
	TWA	435 mg/m3	
		100 ppm	

## Biological limit values

### ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
Xylene (CAS 1330-20-7)	1.5 g/g	Methylhippuric acids	Creatinine in urine	*

\* - For sampling details, please see the source document.

## Exposure guidelines

### Canada - Alberta OELs: Skin designation

Naphthalene (CAS 91-20-3)

Can be absorbed through the skin.

### Canada - British Columbia OELs: Skin designation

Naphthalene (CAS 91-20-3)

Can be absorbed through the skin.

### Canada - Manitoba OELs: Skin designation

Naphthalene (CAS 91-20-3)

Can be absorbed through the skin.

### Canada - Ontario OELs: Skin designation

Naphthalene (CAS 91-20-3)

Can be absorbed through the skin.

### Canada - Saskatchewan OELs: Skin designation

Naphthalene (CAS 91-20-3)

Can be absorbed through the skin.

### US ACGIH Threshold Limit Values: Skin designation

Naphthalene (CAS 91-20-3)

Can be absorbed through the skin.

## Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

## Individual protection measures, such as personal protective equipment

### Eye/face protection

Wear safety glasses with side shields (or goggles).

### Skin protection

#### Hand protection

Impervious gloves. Confirm with reputable supplier first.

#### Other

Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended. Use of impervious boots is recommended. As required by employer code.

### Respiratory protection

Where exposure guideline levels may be exceeded, use an approved NIOSH respirator. Respirator should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134), CAN/CSA-Z94.4 and ANSI's standard for respiratory protection (Z88.2).

### Thermal hazards

Not applicable.

## General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace. When using do not eat or drink.

## 9. Physical and Chemical Properties

Appearance	Liquid
Physical state	Liquid.
Form	Liquid.
Color	Amber / Green
Odor	Not available.
Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	Not available.
Pour point	Not available.
Specific gravity	Not available.
Partition coefficient (n-octanol/water)	Not available.
Flash point	181.4 °F (83.0 °C) ASTM D93
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.

**Upper/lower flammability or explosive limits**

<b>Flammability limit - lower (%)</b>	Not available.
<b>Flammability limit - upper (%)</b>	Not available.
<b>Explosive limit - lower (%)</b>	Not available.
<b>Explosive limit - upper (%)</b>	Not available.
<b>Vapor pressure</b>	Not available.
<b>Vapor density</b>	Not available.
<b>Relative density</b>	0.8616 @ 23.5°C
<b>Solubility(ies)</b>	Immiscible
<b>Auto-ignition temperature</b>	Not available.
<b>Decomposition temperature</b>	Not available.
<b>Viscosity</b>	15.1 mm <sup>2</sup> /s @ 40°C
<b>Other information</b>	
<b>Explosive properties</b>	Not explosive.
<b>Oxidizing properties</b>	Not oxidizing.
<b>VOC (Weight %)</b>	209 g/L (ASTM D2369)

---

## 10. Stability and Reactivity

---

<b>Reactivity</b>	This product may react with strong oxidizing agents.
<b>Possibility of hazardous reactions</b>	No dangerous reaction known under conditions of normal use.
<b>Chemical stability</b>	Material is stable under normal conditions.
<b>Conditions to avoid</b>	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Do not mix with other chemicals.
<b>Incompatible materials</b>	Strong oxidizing agents.
<b>Hazardous decomposition products</b>	May include and are not limited to: Oxides of carbon.

---

## 11. Toxicological Information

---

<b>Routes of exposure</b>	Eye, Skin contact, Inhalation, Ingestion.	
<b>Information on likely routes of exposure</b>		
<b>Ingestion</b>	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia. May cause stomach distress, nausea or vomiting.	
<b>Inhalation</b>	Prolonged inhalation may be harmful.	
<b>Skin contact</b>	Causes skin irritation. May cause an allergic skin reaction.	
<b>Eye contact</b>	Causes serious eye irritation.	
<b>Symptoms related to the physical, chemical and toxicological characteristics</b>	Aspiration may cause pulmonary edema and pneumonitis. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.	
<b>Information on toxicological effects</b>		
<b>Acute toxicity</b>	May be fatal if swallowed and enters airways. May cause an allergic skin reaction.	
<b>Components</b>	<b>Species</b>	<b>Test Results</b>
3(2H)-Isothiazolone, 4,5-dichloro-2-octyl- (CAS 64359-81-5)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Not available	
<i>Inhalation</i>		
LC50	Rat	0.3 mg/l/4h
<i>Oral</i>		
LD50	Not available	
Copper(II) 8-hydroxyquinolinatate (CAS 10380-28-6)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Rabbit	> 2000 mg/kg

Components	Species	Test Results
<i>Inhalation</i>		
LC50	Rat	0.2 mg/l/4h
<i>Oral</i>		
LD50	Rat	9930 mg/kg 4700 mg/kg
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Rabbit	> 2000 mg/kg > 2000 mg/kg, 24 Hours
<i>Inhalation</i>		
LC50	Rat	2.2 mg/L, 4 Hours 2.2 mg/l/4h
<i>Oral</i>		
LD50	Rat	> 5000 mg/kg > 2000 mg/kg
Hexanoic acid, 2-ethyl-, zirconium salt (CAS 22464-99-9)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Guinea pig Rat	6300 mg/kg > 2000 mg/kg, 24 Hours
<i>Inhalation</i>		
LC50	Rat	> 4.3 mg/L, 4 Hours
<i>Oral</i>		
LD50	Rat	> 5000 mg/kg
Naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Rabbit	> 6000 mg/kg, 24 Hours, ECHA > 3750 mg/kg, 24 Hours, ECHA > 3000 mg/kg, 24 Hours, ECHA > 2000 mg/kg, ECHA > 2000 mg/kg, 24 Hours, ECHA > 1900 mg/kg, 24 Hours, ECHA
<i>Inhalation</i>		
LC50	Rat	> 8530 mg/m3, 4 Hours, ECHA > 7970 mg/m3, 4 Hours, ECHA > 7630 mg/m3, 4 Hours, ECHA > 7300 mg/m3, 4 Hours, ECHA > 5830 mg/m3, 4 Hours, ECHA > 5740 mg/m3, 4 Hours, ECHA > 5610 mg/m3, 4 Hours, ECHA > 5470 mg/m3, 4 Hours, ECHA > 5300 mg/m3, 4 Hours, ECHA > 5280 mg/m3, 4 Hours, ECHA > 5260 mg/m3, 4 Hours, ECHA > 5250 mg/m3, 4 Hours, ECHA



**Components****Species****Test Results**

		> 5240 mg/m3, 4 Hours, ECHA
		> 5220 mg/m3, 4 Hours, ECHA
		> 5200 mg/m3, 4 Hours, ECHA
		> 5170 mg/m3, 4 Hours, ECHA
		> 5160 mg/m3, 4 Hours, ECHA
		> 5100 mg/m3, 4 Hours, ECHA
		> 5080 mg/m3, 4 Hours, ECHA
		> 5050 mg/m3, 4 Hours, ECHA
		> 5040 mg/m3, 4 Hours, ECHA
		> 5020 mg/m3, 4 Hours, ECHA
		> 5000 mg/m3, 4 Hours, ECHA
		> 4980 mg/m3, 4 Hours, ECHA
		> 4970 mg/m3, 4 Hours, ECHA
		> 4420 mg/m3, 4 Hours, ECHA
		> 5.4 mg/L, 4 Hours, ECHA
		> 5.1 mg/L, 4 Hours, ECHA
		> 5.1 mg/L, 4 Hours, ECHA
		> 5 mg/L, 4 Hours, ECHA
		> 5 mg/L, 4 Hours, ECHA
		>= 5060 mg/m3, 4 Hours, ECHA
<i>Oral</i> LD50	Rat	> 7000 mg/kg, ECHA
		> 6000 mg/kg, ECHA
		> 5570 mg/kg, ECHA
		> 5200 mg/kg, ECHA
		> 5000 mg/kg, ECHA
		> 4800 mg/kg, ECHA
		> 4500 mg/kg, ECHA
		> 25 ml/kg, HSDB
		14063 mg/kg, ECHA
		6620 mg/kg, ECHA
		5800 mg/kg, ECHA
		5390 mg/kg, ECHA
		4820 mg/kg, ECHA
Paraffin wax (CAS 8002-74-2)		
<b>Acute</b>		
<i>Dermal</i> LD50	Rabbit	> 3600 mg/kg, 24 Hours, ECHA
		> 4 ml/kg, 24 Hours, ECHA
	Rat	> 2000 mg/kg, 24 Hours, ECHA
<i>Inhalation</i> LC50	Not available	
<i>Oral</i> LD50	Dog	> 25 ml/kg, ECHA
	Rat	> 5000 mg/kg
		> 60 ml/kg, ECHA
		> 10 ml/kg, ECHA
		> 5 ml/kg, ECHA

Components	Species	Test Results
Phosphoric acid, 2-ethylhexyl ester (CAS 12645-31-7)		10000 mg/kg, ECHA
<b>Acute</b>		
<i>Dermal</i>		
LC50	Not available	
<i>Inhalation</i>		
LC50	Not available	
<i>Oral</i>		
LD50	Rat	2500 mg/kg
Slack wax (petroleum) (CAS 64742-61-6)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Rabbit	> 2000 mg/kg, 24 Hours
<i>Inhalation</i>		
LC50		
<i>Oral</i>		
LD50	Rat	> 5000 mg/kg
Xylene (CAS 1330-20-7)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Rabbit	> 5000 ml/kg, 4 Hours, ECHA > 43 g/kg, HSDB 12126 mg/kg, 24 Hours, ECHA
<i>Inhalation</i>		
LC50	Mouse	3907 ppm, 6 Hours, HSDB 3907 mg/L, 6 Hours, HSDB
	Rat	6700 ppm, 4 Hours, ECHA 6580 ppm, 4 Hours, ECHA 6350 ppm, 4 Hours, ECHA/HSDB 6247 ppm, 4 Hours, ECHA 5922 ppm, 4 Hours, ECHA
<i>Oral</i>		
LD50	Mouse	5627 mg/kg, ECHA/HSDB 5251 mg/kg, ECHA
	Rat	> 4000 mg/kg, ECHA 6670 mg/kg, HSDB 4300 mg/kg, ECHA/HSDB 3523 mg/kg 10 ml/kg, ECHA
<b>Skin corrosion/irritation</b>	Causes skin irritation.	
<b>Exposure minutes</b>	Not available.	
<b>Erythema value</b>	Not available.	
<b>Oedema value</b>	Not available.	
<b>Serious eye damage/eye irritation</b>	Causes serious eye irritation.	
<b>Corneal opacity value</b>	Not available.	
<b>Iris lesion value</b>	Not available.	
<b>Conjunctival reddening value</b>	Not available.	

<b>Conjunctival oedema value</b>	Not available.	
<b>Recover days</b>	Not available.	
<b>Respiratory or skin sensitization</b>		
<b>Respiratory sensitization</b>	Not a respiratory sensitizer.	
<b>Skin sensitization</b>	May cause an allergic skin reaction.	
<b>Mutagenicity</b>	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
<b>Carcinogenicity</b>	See below.	
<b>ACGIH Carcinogens</b>		
Benzene, ethyl- (CAS 100-41-4)	A3	Confirmed animal carcinogen with unknown relevance to humans.
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	A2	Suspected human carcinogen.
Naphthalene (CAS 91-20-3)	A3	Confirmed animal carcinogen with unknown relevance to humans.
<b>Canada - Manitoba OELs: carcinogenicity</b>		
ETHYL BENZENE (CAS 100-41-4)		Confirmed animal carcinogen with unknown relevance to humans.
MINERAL OIL, EXCLUDING METAL WORKING FLUIDS, POORLY AND MILDLY REFINED (CAS 64742-55-8)		Suspected human carcinogen.
NAPHTHALENE (CAS 91-20-3)		Confirmed animal carcinogen with unknown relevance to humans.
<b>IARC Monographs. Overall Evaluation of Carcinogenicity</b>		
Benzene, ethyl- (CAS 100-41-4)	Volume 77 - 2B	Possibly carcinogenic to humans.
Copper(II) 8-hydroxyquinolate (CAS 10380-28-6)	Volume 15, Supplement 7 - 3	Not classifiable as to carcinogenicity to humans.
Naphthalene (CAS 91-20-3)	Volume 82 - 2B	Possibly carcinogenic to humans.
Xylene (CAS 1330-20-7)	Volume 47, Volume 71 - 3	Not classifiable as to carcinogenicity to humans.
<b>US - California Proposition 65 - CRT: Listed date/Carcinogenic substance</b>		
Benzene, ethyl- (CAS 100-41-4)		
Naphthalene (CAS 91-20-3)		
<b>US NTP Report on Carcinogens: Anticipated carcinogen</b>		
Naphthalene (CAS 91-20-3)	Reasonably Anticipated to be a Human Carcinogen.	
<b>US NTP Report on Carcinogens: Known carcinogen</b>		
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	Known To Be Human Carcinogen.	
<b>US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)</b>		
	Not listed.	
<b>Reproductive toxicity</b>	Suspected of damaging fertility or the unborn child.	
<b>Teratogenicity</b>	Xylene is considered fetotoxic in humans, based on observations of reduced fetal weight, delayed ossification and persistent behavioural effects in animal studies in the absence of maternal toxicity.	
<b>Specific target organ toxicity - single exposure</b>	Not classified.	
<b>Specific target organ toxicity - repeated exposure</b>	Not classified.	
<b>Aspiration hazard</b>	May be fatal if swallowed and enters airways.	
<b>Chronic effects</b>	Prolonged inhalation may be harmful.	

---

## 12. Ecological Information

---

<b>Ecotoxicity</b>	See below		
<b>Ecotoxicological data</b>			
<b>Components</b>		<b>Species</b>	<b>Test Results</b>
Copper(II) 8-hydroxyquinolate (CAS 10380-28-6)			
<b>Aquatic</b>			
Fish	LC50	Rainbow trout, donaldson trout (Oncorhynchus mykiss)	0.062 mg/L, 96 hours
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)			
Crustacea	EC50	Daphnia	1000 mg/L, 48 Hours
Naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9)			
<b>Aquatic</b>			
Crustacea	EC50	Water flea (Daphnia pulex)	2.7 - 5.1 mg/L, 48 hours

Components	Species	Test Results
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)
		8.8 mg/L, 96 hours
		8.8 mg/L, 96 hours
Xylene (CAS 1330-20-7)		
<b>Aquatic</b>		
Fish	LC50	Bluegill (Lepomis macrochirus)
		7.711 - 9.591 mg/L, 96 hours
<b>Persistence and degradability</b>	No data is available on the degradability of this product.	
<b>Bioaccumulative potential</b>		
<b>Mobility in soil</b>	No data available.	
<b>Mobility in general</b>	Not available.	
<b>Other adverse effects</b>	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation)	

### 13. Disposal Considerations

<b>Disposal instructions</b>	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.
<b>Local disposal regulations</b>	Dispose in accordance with all applicable regulations.
<b>Hazardous waste code</b>	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
<b>Waste from residues / unused products</b>	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
<b>Contaminated packaging</b>	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

### 14. Transport Information

<b>Transport of Dangerous Goods (TDG) Proof of Classification</b>	Classification Method: Classified as per Part 2, Sections 2.1 – 2.8 of the Transportation of Dangerous Goods Regulations. If applicable, the technical name and the classification of the product will appear below.
<b>U.S. Department of Transportation (DOT)</b>	Not regulated as dangerous goods.
<b>Transportation of Dangerous Goods (TDG - Canada)</b>	Not regulated as dangerous goods.

### 15. Regulatory Information

<b>Canadian federal regulations</b>	This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.	
<b>Canada CEPA Schedule I: Listed substance</b>		
Naphthalene (CAS 91-20-3)		Listed.
<b>Canada DSL Challenge Substances: Listed substance</b>		
Naphthalene (CAS 91-20-3)		Listed.
<b>Canada NPRI VOCs with Additional Reporting Requirements: Mass reporting threshold/Identification Number</b>		
Naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9)		1 TONNES
Xylene (CAS 1330-20-7)		1 TONNES
<b>Export Control List (CEPA 1999, Schedule 3)</b>	Not listed.	
<b>Greenhouse Gases</b>	Not listed.	
<b>Precursor Control Regulations</b>	Not regulated.	
<b>WHMIS 2015 Exemptions</b>	Not applicable	
<b>US federal regulations</b>	This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.	
<b>TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)</b>	Not regulated.	
<b>CERCLA Hazardous Substance List (40 CFR 302.4)</b>		
Benzene, ethyl- (CAS 100-41-4)		Listed.
Copper(II) 8-hydroxyquinolate (CAS 10380-28-6)		Listed.

Naphthalene (CAS 91-20-3) Listed.  
Xylene (CAS 1330-20-7) Listed.

**US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)**

Not listed.

**Superfund Amendments and Reauthorization Act of 1986 (SARA)**

**Hazard categories** Immediate Hazard - Yes  
Delayed Hazard - Yes  
Fire Hazard - Yes  
Pressure Hazard - No  
Reactivity Hazard - No

**SARA 302 Extremely hazardous substance** No

**SARA 311/312 Hazardous chemical** No

**SARA 313 (TRI reporting)**  
Not regulated.

**Other federal regulations**

**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Benzene, ethyl- (CAS 100-41-4)  
Naphthalene (CAS 91-20-3)  
Xylene (CAS 1330-20-7)

**Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)**

Not regulated.

**Clean Water Act (CWA) Section 112(r) (40 CFR 68.130)** Hazardous substance  
Priority pollutant  
Toxic pollutant

**US state regulations** See below

**US - California Hazardous Substances (Director's): Listed substance**

Benzene, ethyl- (CAS 100-41-4) Listed.  
Copper(II) 8-hydroxyquinolate (CAS 10380-28-6) Listed.  
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8) Listed.  
Hexanoic acid, 2-ethyl-, zirconium salt (CAS 22464-99-9) Listed.  
Naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9) Listed.  
Naphthalene (CAS 91-20-3) Listed.  
Paraffin wax (CAS 8002-74-2) Listed.  
Xylene (CAS 1330-20-7) Listed.

**US - Illinois Chemical Safety Act: Listed substance**

Benzene, ethyl- (CAS 100-41-4)  
Copper(II) 8-hydroxyquinolate (CAS 10380-28-6)  
Naphthalene (CAS 91-20-3)  
Xylene (CAS 1330-20-7)

**US - Louisiana Spill Reporting: Listed substance**

Benzene, ethyl- (CAS 100-41-4) Listed.  
Copper(II) 8-hydroxyquinolate (CAS 10380-28-6) Listed.  
Naphthalene (CAS 91-20-3) Listed.  
Xylene (CAS 1330-20-7) Listed.

**US - Michigan Critical Materials Register: Parameter number**

Copper(II) 8-hydroxyquinolate (CAS 10380-28-6)  
Xylene (CAS 1330-20-7)

**US - Minnesota Haz Subs: Listed substance**

Benzene, ethyl- (CAS 100-41-4) Listed.  
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8) Listed.  
Hexanoic acid, 2-ethyl-, zirconium salt (CAS 22464-99-9) Listed.  
Naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9) Listed.  
Naphthalene (CAS 91-20-3) Listed.  
Paraffin wax (CAS 8002-74-2) Listed.  
Xylene (CAS 1330-20-7) Listed.

**US - New Jersey RTK - Substances: Listed substance**

Benzene, ethyl- (CAS 100-41-4)

Copper(II) 8-hydroxyquinolate (CAS 10380-28-6)  
 Naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9)  
 Naphthalene (CAS 91-20-3)  
 Paraffin wax (CAS 8002-74-2)  
 Xylene (CAS 1330-20-7)

**US - North Carolina Toxic Air Pollutants: Listed substance**

Xylene (CAS 1330-20-7)

**US - Texas Effects Screening Levels: Listed substance**

3(2H)-Isothiazolone, 4,5-dichloro-2-octyl- (CAS 64359-81-5) Listed.  
 Benzene, ethyl- (CAS 100-41-4) Listed.  
 Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8) Listed.  
 Hexanoic acid, 2-ethyl-, zirconium salt (CAS 22464-99-9) Listed.  
 Naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9) Listed.  
 Naphthalene (CAS 91-20-3) Listed.  
 Paraffin wax (CAS 8002-74-2) Listed.  
 Slack wax (petroleum) (CAS 64742-61-6) Listed.  
 Xylene (CAS 1330-20-7) Listed.

**US - Washington Chemical of High Concern to Children: Listed substance**

Benzene, ethyl- (CAS 100-41-4)

**US. Massachusetts RTK - Substance List**

Benzene, ethyl- (CAS 100-41-4)  
 Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)  
 Naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9)  
 Naphthalene (CAS 91-20-3)  
 Paraffin wax (CAS 8002-74-2)  
 Xylene (CAS 1330-20-7)

**US. New Jersey Worker and Community Right-to-Know Act**

Benzene, ethyl- (CAS 100-41-4)  
 Copper(II) 8-hydroxyquinolate (CAS 10380-28-6)  
 Naphthalene (CAS 91-20-3)  
 Xylene (CAS 1330-20-7)

**US. Pennsylvania Worker and Community Right-to-Know Law**

Benzene, ethyl- (CAS 100-41-4)  
 Copper(II) 8-hydroxyquinolate (CAS 10380-28-6)  
 Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)  
 Naphthalene (CAS 91-20-3)  
 Paraffin wax (CAS 8002-74-2)  
 Xylene (CAS 1330-20-7)

**US. Rhode Island RTK**

Benzene, ethyl- (CAS 100-41-4)  
 Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)  
 Hexanoic acid, 2-ethyl-, zirconium salt (CAS 22464-99-9)  
 Naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9)  
 Naphthalene (CAS 91-20-3)  
 Paraffin wax (CAS 8002-74-2)  
 Xylene (CAS 1330-20-7)

**US. California Proposition 65**



**WARNING:** This product can expose you to chemicals including Naphthalene, which is known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

**US - California Proposition 65 - CRT: Listed date/Carcinogenic substance**

Benzene, ethyl- (CAS 100-41-4) Listed: June 11, 2004  
 Naphthalene (CAS 91-20-3) Listed: April 19, 2002

**Inventory status**


Country(s) or region	Inventory name	On inventory (yes/no)*
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

## 16. Other Information

LEGEND	
Severe	4
Serious	3
Moderate	2
Slight	1
Minimal	0

HEALTH	*	2
FLAMMABILITY		2
PHYSICAL HAZARD		0
PERSONAL PROTECTION		X



**Disclaimer**

The information in the sheet was written based on the best knowledge and experience currently available. Information contained herein was obtained from sources considered technically accurate and reliable. While every effort has been made to ensure full disclosure of product hazards, in some cases data is not available and is so stated. Since conditions of actual product use are beyond control of the supplier, it is assumed that users of this material have been fully trained according to the requirements of all applicable legislation and regulatory instruments. No warranty, expressed or implied, is made and supplier will not be liable for any losses, injuries or consequential damages which may result from the use of or reliance on any information contained in this document.

**Issue date**

06-March-2019

**Version #**

02

**Effective date**

11-December-2018

**Prepared by**

Dell Tech Laboratories, Ltd. Phone: (519) 858-5021

**Other information**

For an updated SDS, please contact the supplier/manufacturer listed on the first page of the document.