



When other wood coatings fail  
professionals turn to Cutek

## FACTSHEET No 5 Cutek Proclean

### Cuttek ProClean Professional Wood Cleaner

Want to revive your deck or cladding that has greyed off? Need to know how to restore decks, cladding and screens?

The solution is **Cuttek Proclean**. This professional grade wood restoration product will brighten, clean and restore wood to look like new, ready for coating with **Cuttek** oils.

Use when wood is significantly grey and weathered, or to remove stubborn stains caused by tannin, iron, water, resin, mold & fungus etc.

Always patch test **Proclean** before use.

- Professional grade wood restoration cleaner that keeps working for up to 24 hours.
- Removes stubborn stains, including iron and water stains
- Restores oxidized and grey timber while enhancing the grain



### Before you apply



Because of the wide variation in wood species and types of stains, always test **Cuttek Proclean** before starting your project. This will help you determine how much time you'll need to leave **Cuttek Proclean** on the wood before rinsing and how much **Cuttek Proclean** you will need for the job.

### How to apply

Unlike bleach, **Cuttek Proclean** is not considered a strong defoliant, however, we recommend using absorbent drop cloths to protect delicate and/or adjacent vegetation and surfaces.

For best results use **Cuttek Proclean** as supplied and stir it well before use. Sometimes, if you're working with an easy to clean surface **Cuttek Proclean** can be diluted with water. If a choice to dilute the product is made, always test to determine if the dilution being used is effective in cleaning.

## Application

Before you begin, note the hazards and precautions on this website and the jug labelling, and ensure that you use the correct safety equipment as detailed in the Safety Data Sheet.

After testing a patch of wood and determining the required dilution, if any, apply **Cutek Proclean** liberally to a pre-wetted wood substrate with brush, roller, or garden sprayer.

Let **Cutek Proclean** do most of the work by letting it sit on the surface for 10 minutes – 8 hours, or such time as deemed to be necessary by the test procedure. It may be necessary to scrub stubborn stains moderately with a stiff fibre brush and/or leave on the surface for up to 24hrs.

## Removal

Once **Cutek Proclean** has cleaned the wood, it must be power rinsed off thoroughly. For best results, power rinse with a high-pressure washer set to under 750 p.s.i. (50 bar), with a fan jet pattern to avoid damage to the wood fibre.

Clean from the lowest point and work upwards methodically. **ALWAYS** clean off with a water jet that produces a “putty knife” shaped fan that is 40–50mm (1.5” - 2”) wide about 100mm (4”) out from jet. Adopt a continuous “mowing action” working with power water fan-jet 100mm (4”) from the face of the substrate. **DO NOT** use “turbojets” on wood.

**CAUTION** must be used when cleaning soft timber to reduce the pressure and avoid damaging the sapwood.

The longer that **Cutek Proclean** is left on the substrate, the greater the rinse time required.

Additionally, certain types of wood surfaces may leave a raised grain effect after stripping is completed. Sanding or poly pad scrubbing may be required to smooth out this condition.

If **Cutek Proclean** is being used to remove mill glaze (a smooth glossy surface found on smooth newly sawn wood, which is impervious to most coatings) use the same procedure as above.

## Recoating with Cutek Extreme oil

Following the restoration of the wood with **Cutek Proclean**, it is important to complete the restoration process by coating the wood with **Cutek Extreme** oil, following the procedures detailed on this website.

Not treating the wood after cleaning will result in the weathering process occurring more rapidly than prior to cleaning.

## Precautions

**Cutek Proclean** will make surfaces slippery so **DO NOT** walk on the surface until it is dry. Water flush all equipment, vegetation, paths, concrete, asphalt, and other adjacent surfaces immediately upon contact.

Always remember that **Cutek Proclean** is a hazardous chemical, and refer to the health and safety considerations listed in the Safety Data Sheet prior to commencing any project.

Fully protect adjacent surfaces including vegetation and be aware of the potential for wind drift into areas with cars or pedestrian traffic when rinsing or applying.

Never leave behind any containers or equipment, and appropriately label any containers of residue for disposal.