




SAFETY DATA SHEET

1. Identification

Product identifier	CUTEK Colourtone Blondetone, Whitewash
Other means of identification	Not available.
Recommended use	Colourtone pigment for addition into Cutek Oils.
Recommended restrictions	None known.
Manufacturer information	Deck Source Inc. 647 Welham Road, Unit 11 Barrie, ON L4N 0B7 CA Phone: 1-844-442-8835 Emergency Phone: 613-996-6666 (CANUTEC)
Supplier	See above.

2. Hazard identification

Physical hazards	Flammable liquids	Category 4
Health hazards	Specific target organ toxicity, single exposure	Category 3 narcotic effects
Environmental hazards	Not classified.	
WHMIS 2015 defined hazards	Not classified	
Label elements		
Signal word	Warning	
Hazard statement	Combustible liquid. May cause drowsiness or dizziness.	
Precautionary statement		
Prevention	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid breathing mist or vapor. Use only outdoors or in a well-ventilated area. Wear protective gloves, protective clothing, eye protection and face protection.	
Response	In case of fire: Use carbon dioxide, dry chemical, water spray, or foam to extinguish. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell.	
Storage	Store in a well-ventilated place. Keep container tightly closed. Store locked up.	
Disposal	Dispose of container in accordance with local, regional, national and international regulations.	
WHMIS 2015: Health Hazard(s) not otherwise classified (HHNOC)	None known	
WHMIS 2015: Physical Hazard(s) not otherwise classified (PHNOC)	None known	
Hazard(s) not otherwise classified (HNOC)	None known.	
Supplemental information	None.	

3. Composition/Information on ingredients

Mixture

Chemical name	Common name and synonyms	CAS number	%
Naphtha (petroleum), hydrotreated heavy		64742-48-9	10 - 30 *
Titanium oxide		13463-67-7	65 - 85 *

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Composition comments	*CANADA GHS: The exact percentage (concentration) of composition has been withheld as a trade secret. US GHS: The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.
-----------------------------	--

4. First-aid measures

Inhalation	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell.
Skin contact	Flush with cool water. Wash with soap and water. Obtain medical attention if irritation persists.
Eye contact	Flush with cool water. Remove contact lenses, if applicable, and continue flushing. Obtain medical attention if irritation persists.
Ingestion	Rinse mouth. Do not induce vomiting. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Never give anything by mouth if victim is unconscious or is convulsing. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Direct contact with eyes may cause temporary irritation.
Indication of immediate medical attention and special treatment needed	Treat patient symptomatically.
General information	If you feel unwell, seek medical advice (show the label where possible). Show this safety data sheet to the doctor in attendance. Avoid contact with eyes and skin. Keep out of reach of children.

5. Fire-fighting measures

Suitable extinguishing media	Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	The product is combustible, and heating may generate vapors which may form explosive vapor/air mixtures. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire-fighting equipment/instructions	In case of fire and/or explosion do not breathe fumes.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	Combustible liquid.
Hazardous combustion products	May include and are not limited to: Oxides of carbon.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Ensure adequate ventilation. Avoid breathing mist or vapor. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water. Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.
Environmental precautions	Do not discharge into lakes, streams, ponds or public waters.

7. Handling and storage

Precautions for safe handling	Keep away from open flames, hot surfaces and sources of ignition. Wear appropriate personal protective equipment. Provide adequate ventilation. Avoid prolonged exposure. Observe good industrial hygiene practices. Wash thoroughly after handling. When using, do not eat, drink or smoke.
Conditions for safe storage, including any incompatibilities	Keep away from heat, sparks and open flame. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS). Keep out of reach of children. Store locked up.

8. Exposure controls/Personal protection

Occupational exposure limits

Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)

Components	Type	Value
Titanium oxide (CAS 13463-67-7)	TWA	10 mg/m3

Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

Components	Type	Value	Form
Titanium oxide (CAS 13463-67-7)	TWA	3 mg/m3	Respirable fraction.
		10 mg/m3	Total dust.

Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)

Components	Type	Value
Titanium oxide (CAS 13463-67-7)	TWA	10 mg/m3

Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)

Components	Type	Value
Naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9)	TWA	525 mg/m3
Titanium oxide (CAS 13463-67-7)	TWA	10 mg/m3

Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety)

Components	Type	Value	Form
Titanium oxide (CAS 13463-67-7)	TWA	10 mg/m3	Total dust.

Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21)

Components	Type	Value
Titanium oxide (CAS 13463-67-7)	15 minute	20 mg/m3
	8 hour	10 mg/m3

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Titanium oxide (CAS 13463-67-7)	PEL	15 mg/m3	Total dust.

US. OSHA Table Z-3 (29 CFR 1910.1000)

Components	Type	Value	Form
Titanium oxide (CAS 13463-67-7)	TWA	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.

US. ACGIH Threshold Limit Values

Components	Type	Value
Titanium oxide (CAS 13463-67-7)	TWA	10 mg/m3

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Ensure adequate ventilation.

Individual protection measures, such as personal protective equipment

Eye/face protection

Not normally required under normal use conditions.

Skin protection

Hand protection

Rubber gloves. Confirm with a reputable supplier first.

Other

Not normally required. Avoid contact with eyes and skin.

Respiratory protection	Where exposure guideline levels may be exceeded, use an approved NIOSH respirator. Respirator should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134), CAN/CSA-Z94.4 and ANSI's standard for respiratory protection (Z88.2).
Thermal hazards	Not applicable.
General hygiene considerations	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and immediately after handling the product. When using, do not eat, drink or smoke.

9. Physical and chemical properties

Appearance	Liquid
Physical state	Liquid.
Form	Liquid.
Color	White, Off white
Odor	Not available.
Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	347 - 428 °F (175 - 220 °C)
Pour point	Not available.
Specific gravity	1.2 - 1.4
Partition coefficient (n-octanol/water)	Not available.
Flash point	143.6 °F (62.0 °C)
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	2 - 7 P @25°C
Other information	
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.

10. Stability and reactivity

Reactivity	This product may react with strong oxidizing agents.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Chemical stability	Material is stable under normal conditions.
Conditions to avoid	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	May include and are not limited to: Oxides of carbon.

11. Toxicological information

Routes of exposure	Eye, Skin contact, Inhalation, Ingestion.
---------------------------	---

Information on likely routes of exposure

Ingestion	May cause stomach distress, nausea or vomiting.
Inhalation	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be harmful.
Skin contact	No adverse effects due to skin contact are expected.
Eye contact	Direct contact with eyes may cause temporary irritation.

Symptoms related to the physical, chemical and toxicological characteristics May cause drowsiness and dizziness. Headache. Nausea, vomiting. Coughing.

Information on toxicological effects

Acute toxicity Not classified.

Components	Species	Test Results
Naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	> 6000 mg/kg, 24 Hours, ECHA > 3750 mg/kg, 24 Hours, ECHA > 3000 mg/kg, 24 Hours, ECHA > 2000 mg/kg, ECHA > 2000 mg/kg, 24 Hours, ECHA > 1900 mg/kg, 24 Hours, ECHA
<i>Inhalation</i>		
LC50	Rat	> 8530 mg/m3, 4 Hours, ECHA > 7970 mg/m3, 4 Hours, ECHA > 7630 mg/m3, 4 Hours, ECHA > 7300 mg/m3, 4 Hours, ECHA > 5830 mg/m3, 4 Hours, ECHA > 5740 mg/m3, 4 Hours, ECHA > 5610 mg/m3, 4 Hours, ECHA > 5470 mg/m3, 4 Hours, ECHA > 5300 mg/m3, 4 Hours, ECHA > 5280 mg/m3, 4 Hours, ECHA > 5260 mg/m3, 4 Hours, ECHA > 5250 mg/m3, 4 Hours, ECHA > 5240 mg/m3, 4 Hours, ECHA > 5220 mg/m3, 4 Hours, ECHA > 5200 mg/m3, 4 Hours, ECHA > 5170 mg/m3, 4 Hours, ECHA > 5160 mg/m3, 4 Hours, ECHA > 5100 mg/m3, 4 Hours, ECHA > 5080 mg/m3, 4 Hours, ECHA > 5050 mg/m3, 4 Hours, ECHA > 5040 mg/m3, 4 Hours, ECHA > 5020 mg/m3, 4 Hours, ECHA > 5000 mg/m3, 4 Hours, ECHA > 4980 mg/m3, 4 Hours, ECHA > 4970 mg/m3, 4 Hours, ECHA > 4420 mg/m3, 4 Hours, ECHA > 5.4 mg/L, 4 Hours, ECHA > 5.1 mg/L, 4 Hours, ECHA > 5.1 mg/L, 4 Hours, ECHA

Components	Species	Test Results
		> 5 mg/L, 4 Hours, ECHA
		> 5 mg/L, 4 Hours, ECHA
		>= 5060 mg/m ³ , 4 Hours, ECHA
<i>Oral</i> LD50	Rat	> 7000 mg/kg, ECHA > 6000 mg/kg, ECHA > 5570 mg/kg, ECHA > 5200 mg/kg, ECHA > 5000 mg/kg, ECHA > 4800 mg/kg, ECHA > 4500 mg/kg, ECHA > 25 ml/kg, HSDB 14063 mg/kg, ECHA 6620 mg/kg, ECHA 5800 mg/kg, ECHA 5390 mg/kg, ECHA 4820 mg/kg, ECHA
Titanium oxide (CAS 13463-67-7)		
Acute		
<i>Dermal</i>		
LD50	Not available	
<i>Inhalation</i>		
LC50	Rat	> 6.8 mg/L, 4 Hours, ECHA > 3.6 mg/l/4h, ECHA > 2.3 mg/L, 4 Hours, ECHA 5.1 mg/L, 4 Hours, ECHA 3.4 mg/L, 4 Hours, ECHA
<i>Oral</i> LD50	Mouse Rat	> 5000 mg/kg, ECHA > 25000 mg/kg, ECHA > 11000 mg/kg, ECHA > 5000 mg/kg, ECHA > 2000 mg/kg, ECHA
Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.	
Exposure minutes	Not available.	
Erythema value	Not available.	
Oedema value	Not available.	
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.	
Corneal opacity value	Not available.	
Iris lesion value	Not available.	
Conjunctival reddening value	Not available.	
Conjunctival oedema value	Not available.	
Recover days	Not available.	
Respiratory or skin sensitization		
Canada - Alberta OELs: Irritant		
Titanium oxide (CAS 13463-67-7)	Irritant	
Respiratory sensitization	Not a respiratory sensitizer.	
Skin sensitization	This product is not expected to cause skin sensitization.	
Mutagenicity	Contains < 3% (w/w) DMSO-extract	

Carcinogenicity Contains < 3% (w/w) DMSO-extract
Carbon black is not unbound and in a respirable form within this product. Therefore it is not considered carcinogenic as it is biologically unavailable for the intended product use. Titanium Dioxide is not unbound and in a respirable form within this product. Therefore it is not considered carcinogenic as it is biologically unavailable for the intended product use.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

Titanium oxide (CAS 13463-67-7)

IARC Monographs. Overall Evaluation of Carcinogenicity

Naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9) Volume 47 - 3 Not classifiable as to carcinogenicity to humans.

Titanium oxide (CAS 13463-67-7) Volume 47, Volume 93 - 2B Possibly carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not listed.

Reproductive toxicity Not classified.
Teratogenicity Not available.
Specific target organ toxicity - single exposure May cause drowsiness and dizziness.
Specific target organ toxicity - repeated exposure Not classified.
Aspiration hazard Not an aspiration hazard.
Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity See below

Ecotoxicological data

Components	Species	Test Results
Titanium oxide (CAS 13463-67-7)		
Fish	LC50	Mummichog (<i>Fundulus heteroclitus</i>) > 1000 mg/L, 96 hours
Aquatic		
Crustacea	EC50	Water flea (<i>Daphnia magna</i>) > 1000 mg/L, 48 hours

Persistence and degradability No data is available on the degradability of any ingredients in the mixture.
Bioaccumulative potential No data available.
Mobility in soil No data available.
Mobility in general Not available.
Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations Dispose in accordance with all applicable regulations.
Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

Transport of Dangerous Goods (TDG) Proof of Classification Classification Method: Classified as per Part 2, Sections 2.1 – 2.8 of the Transportation of Dangerous Goods Regulations. If applicable, the technical name and the classification of the product will appear below.

U.S. Department of Transportation (DOT)

Not regulated as dangerous goods.

Transportation of Dangerous Goods (TDG - Canada)

Not regulated as dangerous goods.

15. Regulatory information

Canadian federal regulations This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

Canada CEPA Schedule I: Listed substance

Titanium oxide (CAS 13463-67-7) Listed.

Canada NPRI VOCs with Additional Reporting Requirements: Mass reporting threshold/Identification Number

Naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9) 1 TONNES

Canada Priority Substances List (Second List): Listed substance

Titanium oxide (CAS 13463-67-7) Listed.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

WHMIS 2015 Exemptions Controlled

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance No

SARA 311/312 Hazardous chemical No

SARA 313 (TRI reporting)
Not regulated.

Other federal regulations**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

US state regulations See below

US - Minnesota Haz Subs: Listed substance

Titanium oxide (CAS 13463-67-7) Listed.

US - Texas Effects Screening Levels: Listed substance

Naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9) Listed.

Titanium oxide (CAS 13463-67-7) Listed.

US. Massachusetts RTK - Substance List

Titanium oxide (CAS 13463-67-7)

US. New Jersey Worker and Community Right-to-Know Act

Titanium oxide (CAS 13463-67-7)

US. Pennsylvania Worker and Community Right-to-Know Law

Naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9)

Titanium oxide (CAS 13463-67-7)

US. Rhode Island RTK

Titanium oxide (CAS 13463-67-7)

US. California Proposition 65

WARNING: This product can expose you to chemicals including arsenic, which is known to the State of California to cause cancer, and lead, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Titanium Dioxide is not unbound and in a respirable form within this product. Therefore it is not considered carcinogenic as it is biologically unavailable for the intended product use.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

Titanium oxide (CAS 13463-67-7) Listed: September 2, 2011

Inventory status


Country(s) or region	Inventory name	On inventory (yes/no)*
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	No

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

16. Other information

LEGEND	
Severe	4
Serious	3
Moderate	2
Slight	1
Minimal	0

HEALTH	* 2
FLAMMABILITY	2
PHYSICAL HAZARD	0
PERSONAL PROTECTION	X

**Disclaimer**

Information contained herein was obtained from sources considered technically accurate and reliable. While every effort has been made to ensure full disclosure of product hazards, in some cases data is not available and is so stated. Since conditions of actual product use are beyond control of the supplier, it is assumed that users of this material have been fully trained according to the requirements of all applicable legislation and regulatory instruments. No warranty, expressed or implied, is made and supplier will not be liable for any losses, injuries or consequential damages which may result from the use of or reliance on any information contained in this document.

Issue date

11-December-2019

Version #

01

Effective date

11-December-2019

Prepared by

Dell Tech Laboratories Ltd. Phone: (519) 858-5021

Other information

For an updated SDS, please contact the supplier/manufacturer listed on the first page of the document.